

# Ceramic Ferrule Specifications

Hsin Chun Ceramic Co.

Ferrule Tupe	AΦ	BΦ	CΦ	DΦ	E	F	G	vent no.
SN8	8.6±0.30	11.4±0.35	10.6±0.35	15.8±0.40	4.8±0.20	8.7±0.30	3.2±0.15	12
SN10	10.7±0.35	14.8±0.40	13.3±0.35	18.1±0.45	5.3±0.20	10.1±0.35	4.0±0.15	16
SR10	10.7±0.35	15.0±0.40		18.1±0.45	7.0±0.25	11.0±0.35		12
SN13	13.4±0.40	18.6±0.45	17.1±0.45	23.2±0.50	8.3±0.30	12.0±0.35	4.5±0.20	18
SN16	17.0±0.45	26.2±0.55	20.6±0.50	30.5±0.55	8.5±0.30	13.0±0.35	6.7±0.25	20
SN19	20.6±0.50	26.6±0.55	24.5±0.50	31.5±0.60	12.0±0.35	16.9±0.45	7.5±0.25	20
SN22	23.0±0.50	30.7±0.60	28.3±0.55	39.0±0.65	14.0±0.40	18.8±0.45	10.0±0.30	18
SN25	26.6±0.55	36.3±0.65	31.3±0.60	41.0±0.70	16.0±0.40	21.0±0.50	12.5±0.35	20
DS19	20.6±0.50	30.7±0.60	24.8±0.50	34.0±0.60	10.5±0.35	15.0±0.40	8.0±0.25	8
DS22	23.5±0.50	31.0±0.60	27.1±0.55	35.8±0.65	14.0±0.40	19.0±0.45	7.7±0.25	14
SP20F	19.3±0.45	30.7±0.60	22.2±0.50	33.8±0.60	6.0±0.20	10.0±0.30	6.0±0.20	18
DS16T	17.1±0.45	26.1±0.55	21.2±0.50	30.2±0.55	13.5±0.40	18.0±0.45	7.7±0.25	10
DS19T	20.1±0.50	30.0±0.55	26.5±0.55	35.5±0.65	10.7±0.35	15.7±0.40	7.2±0.25	12
DS22T	23.5±0.50	33.0±0.60	29.0±0.55	40.5±0.70	13.6±0.40	18.2±0.45	7.7±0.25	14
ASB16	16.75±0.45	21.15±0.50	20.0±0.45	26.5±0.55	8.75±0.30	13.4±0.40	6.5±0.25	22
ASB20	21.16±0.50	27.0±0.55	24.2±0.50	32.2±0.60	12.0±0.35	17.2±0.45	8.5±0.30	20

Unit : m/m

SN: STANDARD TYPE  
DS: THROUGH DECK

